



INSTRUCTIONS

Starter Motor

Please Read These First

These instructions are intended as a guide only and are not a substitute for a workshop manual. The fitter must have a degree of mechanical competence. If you are in any doubt as to your ability to fit the part, do not undertake the job.

For more Technical Tips and to register your warranty online visit

www.smpe.co.uk

Contact technical sales on

01527 839307

www.smpe.co.uk

FuelParts^{UK} Intermotor 

Starter Motor

Starter motors are often located in hot and inaccessible locations, it is strongly recommended that the engine be allowed to cool fully before beginning the repair

Before renewing the starter motor check the battery condition and renew/charge it as necessary

Removing the old starter

Disconnect battery earth lead, then disconnect battery live.

Disconnect electrical connections to the starter motor and/or solenoid. Make a careful note of each connection. Check connectors and wires for damage/corrosion correct as required.

Check engine – chassis earth leads

Unbolt and remove starter motor

Check old starter motor for damage that may affect the replacement unit. E.g. excessive dust on the drive gear may indicate a clutch/flywheel fault, Oil/water stains may indicate that the old unit failed due to an engine leak, a blued/burnt starter may indicate either an inherent starting fault or a meshing fault. These faults should be addressed to prevent premature failure. Compare the old unit to the new unit; look for locating dowels/bushes. Swap over and renew if damaged mating surface.

Connecting the new starter

Connect new starter motor, matching the connections from the old unit, ensure that the leads are routed away from any hot/moving surfaces.

Reconnect battery, connecting earth lead last.

Start engine.

Caution

RES3039

Please note this application suffers from steel/dust contamination. This results in failure of the gear mechanism within the starter motor. If the starter motor is renewed without investigating the cause of the dust/debris i.e. careful inspection of the clutch/dual mass flywheel, then failure of the new unit will result, in a very short time

This is not considered a Starter motor fault/warranty failure.
Your warranty will be void if dust contamination is determined to be the cause of failure.